

Rugged-Reliable Two-way Radio



Support LTE(4G)/WCDMA(3G)/GSM(2G) Network

- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform



SE368/SE368A

Handheld Two-way Radio

<http://www.sfecom.cn>

Main Features

- Support LTE(4G)/WCDMA(3G)/GSM(2G) Network
- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform
- With Functional Dispatching System
- GPS Function Optional
- Li-ion Battery Capacity 5200mAh
- Emergency Alarm Function
- Superb Clear and Powerful Audio Output

Accessories



General/Technical Specifications

Model	SE368	SE368A
Working Voltage	DC3.7V	
Working Mode	Semi-Duplex	
Working Temperature	-20 ~ +60 °C	
Storage Temperature	-30 ~ +80 °C	
Battery Capacity	5200mAh	
Antenna Impedence	50Ω	
Audio Output	500mW	
Dimension	52*33*102mm	
Weight	Approx 220g(Battery & Antenna Included)	
Operation System	Linux	Android
Bluetooth	No	Yes
WIFI	No	Yes
GPS	Optional	
Frequency Range	LTE_FDD: B1/B3/B7/B8/B20	LTE_FDD: B1/B3/B5/B7/B8/B20
	WCDMA: B1/B8	WCDMA: B1/B2/B5/B8
	GSM: B3/B8	GSM: B2/B3/B5/B8*
	Other Bands Customized	
RF Power	≤30dBm	
RX Sensitivity	LTE ≤ -96 dBm	LTE ≤ -96 dBm
	WCDMA ≤ -108 dBm	WCDMA ≤ -108 dBm
	GSM ≤ -108 dBm	GSM ≤ -108 dBm

Above specifications are tested according to TIA/EIA-603.
Above specifications are subject to change without any notice due to technology enhancement.